

Isolatoren • insulator/spacers

Merkmale • characteristics:

- Glasfaserverstärktes Polyester
- Farbe: Rot, RAL 3002
- Metrisches Gewinde UNI 4534-64
- glass reinforced polyester
- colour: red, RAL 3002
- female thread inserts metric UNI 4534-64

Microtherm GmbH



Abt. Panta

Taschenwaldstr. 3
D-75181 Pforzheim

Tel.: 07231/787-0

Fax: 07231/787-269

e-mail: panta@microtherm.de



Isolatoren/Insulators

ABMESSUNGEN / DIMENSIONS

TECHNISCHE WERTE / STRENGTH DETAILS

Art.-Nr. Code	H (mm)	E (mm)	D (mm)	Gewinde screw thread	High-Voltage Widerstand resistance für/for 1 Min.	Zugkraft tensile breaking Value Kgs	Drehkraft torque breaking Value Kgs Mtrs	Biegekraft cantilever breaking Kgs
IS20-4	20	19	15	M4	2.50 KV	200,00	1,30	100,00
IS20-6	20	19	15	M6	2.50 KV	200,00	1,60	110,00
IS25-5	25	21	15	M5	2,50 KV	280,00	1,80	140,00
IS25-6	25	21	15	M6	2,50 KV	280,00	1,80	140,00
IS30-6	30	32	23	M6	2.50 KV	500,00	2,00	150,00
IS30-8	30	32	23	M8	2.50 KV	500,00	2,00	150,00
IS30-10	30	32	23	M10				
IS35-6	35	35	25	M6	2.50 KV	600,00	2,50	200,00
IS35-8	35	35	25	M8	2.50 KV	600,00	2,50	200,00
IS35-10	35	35	25	M10	2.50 KV	700,00	4,00	240,00
IS40-8	40	40	30	M8	2.50 KV	1060,00	4,00	330,00
IS40-10	40	40	30	M10	2.50 KV	1060,00	4,50	330,00
IS40-12	40	40	30	M12	2.50 KV	1150,00	5,80	380,00
IS45-8	45	40	30	M8	2.50 KV	1110,00	4,00	320,00
IS45-10	45	40	30	M10	2.50 KV	1050,00	5,00	330,00
IS45-12	45	40	30	M12	2.50 KV			
IS50-8	50	44	33	M8	2.50 KV	1200,00	4,50	300,00
IS50-10	50	44	33	M10	2.50 KV	1350,00	5,50	350,00
IS50-12	50	44	33	M12	2.50 KV	1350,00	5,50	350,00
IS55-8	55	44	40	M8	2.50 KV	1100,00	4,50	300,00
IS55-10	55	44	40	M10	2.50 KV	1120,00	5,40	350,00
IS55-12	55	44	40	M12	2.50 KV	1250,00	5,50	350,00
IS60-8	60	55	40	M8	2.50 KV	1550,00	6,50	420,00
IS60-10	60	55	40	M10	2.50 KV	1550,00	6,50	420,00
IS60-12	60	55	40	M12	2.50 KV	1650,00	7,00	450,00
IC20/25-6	25	20	20	M6				
IC20/30-6	30	20	20	M6	2.50 KV	450,00	2,00	125,00
IC20/35-6	35	20	20	M6	2.50 KV	450,00	2,00	100,00
IC20/40-6	40	20	20	M6	2.50 KV	550,00	2,00	105,00
IC20/50-6	50	20	20	M6	2.50 KV	500,00	2,00	120,00

Andere Abmessungen / Typen auf Anfrage
Other Dimensions / types on request